



For Machinists. By Machinists.

VMC 4020_{B-II}

CNC VERTICAL MACHINING CENTER with FADAL 64MP CNC CONTROLLER

Specifications

TRAVEL	
X-axis Travel (in.)	40
Y-axis Travel (in.)	20
Z-axis Travel (in.)	20/30*
Spindle nose to table (in.)	5-25/5-35*
Spindle center to column (in.)	21.25
TABLE	
Table Dimensions (in.)	47.25 x 19.75
T-Slot Dimensions (in.)	(5) 3.75 x .709 x 1.25
Max. Table Load (lbs.)	1,320
SPINDLE	
Spindle Type	Cat-40/BT-40*
Spindle Speed (RPM)	10,000/15,000*
Spindle Torque (ft. lbs.)	175/220*
Spindle Motor (HP) Peak	15/22.5*
FEED	
Rapid Traverse Rate X,Y & Z (IPM)	1,000 / 1,000 / 1,000
Ballscrew Diameter X,Y & Z Axis (mm)	40
ATC	
Tool Capacity	24/30*/40*
Tool Change Type	Dual Arm
Max. Tool Weight (lbs.)	15
Max. Tool Diameter (in.) (with adjacent tool)	4.9 (3.1)
Max. Tool Length (in.)	13.5
Tool Selection Method	Random
OTHER	
Machine Dimensions L x W x H (in.)	109 x 87 x 110
with Chip Conveyor	155 x 87 x 110
Machine Weight (lbs.)	11,770

STANDARD FEATURES

Box Way Construction
Spindle Oil Cooler
LED Work Lamp
Fully Enclosed
Spindle Air Blast
Automatic PDI Lubrication System
Operation Indication Lamp
Rigid Tapping



OPTIONAL FEATURES

Chip Conveyor BT40 High Torque (22.5hp peak) Extended Z Axis 30" 4th Axis Ready 5th Axis Ready RTCP
FR-8 Rotary Table
FTR-8 Tilting Table
FR-5C Rotary Table
Remote MPG
Chip Wash Down System

OPTIONAL PROBING

Tool Pre-Setter (wired)
Tool Pre-Setter (wireless)
X, Y, Z Coordinate (wireless)

FADAL 64MP CONTROLLER

Backward Compatible 88HS & MP Memory 256mb 2000 Blocks/sec Look Ahead Networking & USB Ports High Speed Machining



Authorized Fadal Dealer



www.Fadal.com 844.323.2526